



AUTOMATIC GUILLOTINE TYPE GA118

- a Automatic guillotine for low pressure hoses up from 11 to 40mm



02 / 11 / 2019 19 : 41 : 51 Powered by SERAD V1.0.7

CLAVEL VIDEOJET Connecté Manque encrs Etat: Default
Ready Erreur Puissance axe tube

Nomenclature: Quantité: 1

Name	Tube	Length	Slide	Socket mark	Dist	Tox	Ext1	Ext2	Number	Delay	Size	Dose
Touze 1	48.0	10	1.0	FALSE	0.0		10		10	0.0	5x5	10
elastique	8.0	200	1.0	FALSE	0.0		20		20	0.0	5x5	0
elastique	23.0	200	1.0	FALSE	0.0		20		20	0.0	5x5	0

Fichier Ajouter Modifier Supprimer Tout effacer Remise à zéro Reprise Configuration Alarmes

TECHNICAL SPECIFICATIONS

- Cutting operation with a lubricated circular blade numerically controlled
- Hose driven by a caterpillar system digitally controlled
- Tightening of the caterpillar system digitally controlled
- Positioning of the coil turret with digitally controlled
- Maximum uncoiling speed: 60 meters / minute
- Power supply: 400V TRI - 50hZ
- Air supply: 6 bars
- Product guided by a 12-positions coil turret from Ø11mm to 40mm (others diameters on request)
- capacity: 1000 programs : The operator selects one program number and enters the number of parts
 - Some messages appear on the screen, guide the operator and indicate defaults
 - Automatic cutting operation
 - Automatic loading and evacuation of the products
- Dimensions: H x W x L : 1750 x 820 x 1650mm
- Weight: 45kg

